

2TPH Cow Dung Crushing Machine Agricultural Waste Urea Crusher

Basic Information

Place of Origin: China
Brand Name: TONGDA
Certification: CE,ISO
Model Number: TDNSF-400

Minimum Order Quantity:

• Packaging Details: According to customer requirements

• Delivery Time: 5-10 days

• Payment Terms: L/C, D/A, D/P, T/T, Western Union,

MoneyGram

Supply Ability: 100 units per month



Product Specification

Product Name: Urea Crusher Machine
 Function: Producing Fertilizer
 Core Components: Gear, Motor, Engine

• Capacity(ton/h): 1-2ton/h

Machine Type: Fertilizer CrushingKey Selling Points: Easy To Operate

Highlight: 2TPH Cow Dung Crushing Machine,

Agricultural Waste Urea Crusher,

Fertilizer Urea Crusher



More Images





Product Description

Agricultural Waste Urea Crusher Animal Manure Crushing Machine For Sale Product introduction:

- 1. Urea crusher mainly uses the grinding and cutting of the gap between the roller and the concave plate.
- 2. The clearance size determines the degree of material crushing, and the drum speed and diameter can be adjustable.
- 3. When the urea enters the body, it hits the body wall and the baffle and is broken. Then it is ground into powder through the rack between the roller and the concave plate.
- 4. The clearance of the concave plate shall be adjustable to the extent of crushing by the regulating mechanism within 3-12 mm, and the feeding port regulator can control the production volume.

Model	Central	Capacity(t/h)	Inlet	Discharging	Motor
	Distance(mm)		Granularity(mm	Granularity(mm)	Power(kw)
)		
TDNSF-400	400	1	<10	≤1mm(70%~90	7.5
				%)	

Performance characteristics:

- 1. This machine is designed according to the principle of impact crushing, inside and outside of two groups of cage bars for high-speed rotation, material from inside out through the cage bar impact and crushing.
- 2. Simple structure.
- 3. High crushing efficiency.
- 4. Good sealing performance.
- 5. Smooth operation, easy to clean.
- 6. Easy to maintain and other characteristics.



Working principle:

Before use, place the shredder on a certain position in the workshop and connect it to the power source to use. The fineness of pulverization is controlled by the spacing of the two rollers. The smaller the spacing, the finer the fineness, and the relative reduction in output. The better the uniform pulverization effect is, the higher the output. The device can be designed to be mobile according to user requirements, and the user can move the corresponding position when using it, which is very convenient.

FAQ:

1. Are you trading company or manufacturer?

We are a manufacturer with a history over 40 years and have realized one-stop service for design, manufacture, installation, debugging and technical training.

2. How long is the delivery time?

For standard machines or Components, it would be 5-10 days; For non-standard machines and customized machines according to clients specific requirements, it would be appointment time.

3. Do you arrange shipment for the machines?

Yes, we will do that. For FOB or CIF price, we will arrange shipment for you. For EXW price, we will assist you in arranging shipment.

4. How about your product after-sales service?

Normally we provide video and written technical support. If necessary, our engineers can also provide on-site service. Our product accessories can be selected according to the actual needs of the customer to choose the most appropriate way to deliver.

5. What kinds of certificate you have?

ISO 9001: 2015 SGS and we can make other certificates according to customers' detailed requirements.

6. How to guarantee the quality and operation before loading?

We have our own quality control department and have advance quality control stystem while from raw materials to finished products. All the machines and production lines shall be 100% checked and tested before delivery.



TONGDA HEAVY Henan Tongda Heavy Industry Science And Technology Co., Ltd.





