



Pig Manure Solids Separator Chicken Manure Dewatering Machine

Our Product Introduction

for more products please visit us on organicfertilizerequipment.com

Basic Information

- Place of Origin: China
- Brand Name: TONGDA
- Certification: CE, ISO
- Model Number: TDXS-001
- Minimum Order Quantity: 1
- Packaging Details: According to customer requirements
- Delivery Time: 3-7days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 300 units per month



Product Specification

- Product Name: Solid-liquid Separator
- Advantage: Multi Functional
- Mainframe Voltage: 220V, 380V
- Function: Processing Animal Manure, Making Fertilizer
- Inlet Diameter: 76mm
- Drain Outlet Diameter: 102mm
- Highlight: **Pig Manure Solids Separator, Chicken Manure Dewatering Machine, cow dung separator**



Product Description

Cow Manure Dewatering Machine Pig Manure Liquid Solid Separator Machine

The animal waste solid liquid separator can remove acid sludge, dregs, kitchen waste and many other dregs. It separates solids and liquids well. Solids can be used to make organic fertilizers or fuels, and liquids are good materials for irrigation. The animal waste solid liquid separator is designed to reduce the water content of animal manure, such as cow dung, pig manure and chicken manure.

Features:

1. It has the function of sorting and filtering large pieces first, and combines multiple functions such as transmission, pressing, dehydration and sand removal to solve the problems of garbage winding equipment and airtight operation
2. The separation rate of floating, suspended matter and sediments in the pair of feces is more than 95%, and the solid content of the slag is more than 35%.
3. It has automatic liquid level control function, which saves more than 50% of power consumption than similar equipment, low operating cost,
4. The part of the equipment in contact with the processing medium is made of high-quality stainless steel and is passivated by pickling.

Model	TD800	TD1200	TD1600
Voltage(V)	380V		
Main Motor Power(KW)	4	5.5	8.5
Pump Power(KW)	3		
Inlet Dia.(mm)	76	76	75
Outfall Dia.(mm)	152		
Overall Size(mm)	2050*1150*1600	2420*1150*1600	2100*1900*1800
Weight(kgs)	320	380	430
Material	Stainless steel		
Take Original Dung(kg/h)	20	25	35
Produce Dried Dung(kg/h)	6	8	10
Bucket Size(mm)	150*350	150*400	600*1600

Working principle of the product:

1. It is mainly composed of a host, a cutting type submerged pump, a control cabinet, pipelines and other equipment.
2. The working process is as follows: the waste water to be treated is evenly distributed to the inclined screen surface through the overflow weir.
3. Inclined screens can effectively reduce the concentration of suspended solids in water and reduce the processing load of subsequent processes.
4. At the same time, it is also used for solid-liquid separation and recovery of useful substances in industrial production. The equipment has a high degree of automation, low power consumption, and easy operation. Just press the start and stop button to operate.



FAQ:

Q: Can I use this production line to produce multi granularity particles?

Yes, our production line is multifunctional. We can customize ring moulds of different sizes. In this way, you can easily adjust the size of your ball.

Q: I know little about the fertilizer production line. How to choose the most suitable machine?

Just tell us your raw materials, capacity (tons / hour) and the size of the final particle product, and we will choose the machine for you according to your specific situation.

Q: Our workers don't know how to operate the production line. What should I do?

Our engineers will guide on-site workers on how to install machines and build workshops. Then, our engineers will test the production line on site and train your workers how to operate it.

Q: Are you a trading company or a manufacturer?

We have a large factory in Jiaozuo, China, covering an area of 10000 square meters. Welcome to visit.

Q: What's the Production Period of the Fertilizer Machine?

For single fertilizer machine, our production time is 7 days; and for whole fertilizer production line, our production time is no more than 30 days.

Q: What's the Quality Guarantee and Certifications?

all of our machine have passed ISO and CE certification, we can guarantee the highest quality and our warranty time is 5 years after shipment date.



TONGDA HEAVY

Henan Tongda Heavy Industry Science And Technology Co., Ltd.



+8618538527111



admin@hntdfertilizermachine.com



organicfertilizerequipment.com

Xingyang Longgang Development Zone