

Bio Organic Fertilizer Mixer Machine 11 KW SUS304 Horizontal Animal Waste

Basic Information

Place of Origin: China
Brand Name: TONGDA
Certification: CE,ISO
Model Number: TDWJ-7015

Minimum Order Quantity:

Packaging Details: According to customer requirements

• Delivery Time: 5-7 days delivery

• Payment Terms: L/C, D/A, D/P, T/T, Western Union,

MoneyGram

Supply Ability: 100 units per month



Product Specification

Product Name: Fertilizer Horizontal Mixer

• Power: 11 KW

Raw Material: Organic Manure
Range Of Spindle 40 - 70 R.p.m Speed(r.p.m):

Material: SUS304, SUS304L, SUS316

Barrel Volume (L): 1350 L

Highlight: Bio Organic Fertilizer Mixer Machine,
 SUS304 Fertilizer Mixer Machine,

11 KW Horizontal Fertilizer Mixer Machine



More Images



Product Description

Fertilizer Horizontal Mixer Animal Waste Bio Organic Fertilizer Mixer Machine

Fertilizer horizontal mixers are available in a range of sizes and capacities to accommodate different types of operations. Some models are designed for small-scale operations, while others are capable of processing large volumes of fertilizer materials. They are typically used in agricultural operations such as crop production, animal feed production, and horticulture.

In conclusion, a fertilizer horizontal mixer is a versatile and essential piece of equipment in the agricultural industry. Its ability to blend different types of fertilizer materials together quickly and efficiently ensures that crops receive the nutrients they need to grow and thrive. Whether used on a small scale or in large-scale operations, a fertilizer horizontal mixer is an important investment for any agricultural enterprise.

Model	TDWJ-7015	TDWJ-9015	TDWJ-1630
Dimensions(mm)	2350*1200*1000	2300*1200*1000	3950*1720*2100
Motor Power(kw)	7.5	11	22
Speed Reducer Model	ZQ350-23.34	ZQ350-23.34	ZQ500-48.57
Stirring Speed(r/min)	46	39	21
Main Plate Thickness(mm)	4	4	10
Capacity(t/h)	2-3	3-5	10-15

Working principle:

The fertilizer horizontal mixer consists of a horizontal drum or barrel that is rotated around its axis. The drum is typically made of heavy-duty steel and is lined with a wear-resistant material to prevent damage from the abrasive nature of the fertilizer materials. The drum is supported by a series of rollers and is driven by a motor through a gearbox. The speed of rotation can be adjusted to control the mixing process.



FAQ:

1. Are you trading company or manufacturer ?

We are a manufacturer with a history over 40 years and have realized one-stop service for design, manufacture, installation, debugging and technical training.

2. How long is the delivery time?

For standard machines or Components, it would be 5-10 days; For non-standard machines and customized machines according to clients specific requirements, it would be appointment time.

3. Do you arrange shipment for the machines?

Yes, we will do that. For FOB or CIF price, we will arrange shipment for you. For EXW price, we will assist you in arranging shipment.

4. How about your product after-sales service?

Normally we provide video and written technical support. If necessary, our engineers can also provide on-site service. Our product accessories can be selected according to the actual needs of the customer to choose the most appropriate way to deliver.

5. What kinds of certificate you have?

ISO 9001: 2015 SGS and we can make other certificates according to customers' detailed requirements.

6. How to guarantee the quality and operation before loading?

We have our own quality control department and have advance quality control stystem while from raw materials to finished products. All the machines and production lines shall be 100% checked and tested before delivery.



TONGDA HEAVY Henan Tongda Heavy Industry Science And Technology Co., Ltd.



