

SUS304 Horizontal Fertilizer Mixer Machine Equipment 380V 3phase

Basic Information

Place of Origin: China
Brand Name: TONGDA
Certification: CE,ISO
Model Number: TDWJ-7015

Minimum Order Quantity:

Packaging Details: According to customer requirements

Delivery Time: 5-7 days delivery

Payment Terms:
 L/C, D/A, D/P, T/T, Western Union,

MoneyGram

Supply Ability: 100 units per month



Product Specification

Product Name: Horizontal Fertilizer Mixer Machine

Max. Loading Volume (L): 1000 LBarrel Volume (L): 2.3 L

• Usage: Fertilizer And Feed Processing Plants.

Material: SUS304, SUS304L, SUS316

 Voltage: 3phase 380V 50Hz Or Customerized
 Highlight: Horizontal Fertilizer Mixer Equipment, SUS304 Horizontal Fertilizer Mixer Machine,

380V Horizontal Fertilizer Mixer Machine



Product Description

China Manufacturer Horizontal Fertilizer Mixer Machine for Sale

Horizontal fertilizer mixer machine is generally used for the mixing of solid-solid and solid-paste, such as pesticides, food, chemicals, biology, ceramics, livestock breeding, refractory materials, compound fertilizers, and also for the mixing of viscous materials.

Production capacity for horizontal fertilizer mixer machine: 3-15tons

Application: Used in organic fertilizers, compound fertilizers, mixed fertilizers, pesticides, veterinary drugs, food, chemicals, biology, ceramics, livestock breeding, refractory materials, etc.

| Model | TDWJ-7015 | TDWJ-9015 | TDWJ-1630 |
|--------------------------|----------------|----------------|----------------|
| Dimensions(mm) | 2350*1200*1000 | 2300*1200*1000 | 3950*1720*2100 |
| Motor Power(kw) | 7.5 | 11 | 22 |
| Speed Reducer Model | ZQ350-23.34 | ZQ350-23.34 | ZQ500-48.57 |
| Stirring Speed(r/min) | 46 | 39 | 21 |
| Main Plate Thickness(mm) | 4 | 4 | 10 |
| Capacity(t/h) | 2-3 | 3-5 | 10-15 |

Working principle:

The horizontal fertilizer mixer machine device is designed to a internal and external, left and right reverse spiral. When working, the inner spiral drives the material near the shaft to make the axis rotation, and the axial direction is pushed from the inside to the sides. The outer spiral drives the material near the steel wall to make the axis rotation, and the axial direction is pushed from the sides to the inside, last cause the material to circulate in the mixer, sheared and infiltrated, quickly and evenly mixed in a shorter period of time.



FAQ:

1. Are you trading company or manufacturer?

We are a manufacturer with a history over 40 years and have realized one-stop service for design, manufacture, installation, debugging and technical training.

2. How long is the delivery time?

For standard machines or Components, it would be 5-10 days; For non-standard machines and customized machines according to clients specific requirements, it would be appointment time.

3. Do you arrange shipment for the machines?

Yes, we will do that. For FOB or CIF price, we will arrange shipment for you. For EXW price, we will assist you in arranging shipment.

4. How about your product after-sales service?

Normally we provide video and written technical support. If necessary, our engineers can also provide on-site service. Our product accessories can be selected according to the actual needs of the customer to choose the most appropriate way to

5. What kinds of certificate you have?

ISO 9001: 2015 SGS and we can make other certificates according to customers' detailed requirements.

6. How to guarantee the quality and operation before loading?

We have our own quality control department and have advance quality control stystem while from raw materials to finished products. All the machines and production lines shall be 100% checked and tested before delivery.



TONGDA HEAVY Henan Tongda Heavy Industry Science And Technology Co., Ltd.





